

### Amendments to the claims:

This listing of claims will replace all prior versions, and listings, of claims in the application.

Please cancel claims 3-6 without prejudice.

Please add new claim 26.

Please amend claims 1, 7, 8, 9, 10, 16 and 17 as indicated below (material to be inserted is in **bold and underline**, material to be deleted is in ~~[brackets and strikeout]~~):

### Listing of Claims:

1. (Currently amended) A spittoon for servicing a printhead, the spittoon comprising:

a reservoir for a waste ink; and

a precipitating agent within the reservoir, wherein the precipitating agent is a multivalent organic acid that is selected to react with a component of the waste ink to form a precipitate.

2. (Original) The spittoon of claim 1, wherein the precipitating agent is incorporated in an absorbent pad within the reservoir.

3. (Canceled)

4. (Canceled)

5. (Canceled)

6. (Canceled)

7. (Currently amended) The spittoon of claim [6] 1, wherein the precipitating agent is selected from the group consisting of citric acid, succinic acid, and salicylic acid.

8. (Currently amended) A spittoon for servicing a printhead, the spittoon comprising:

a bottom;

one or more walls, each wall having a top edge, the walls in combination with the bottom defining a waste ink reservoir having a capacity; and

an inwardly extending lip at the top edge of at least one wall configured to retain a volume of waste ink when the spittoon is tilted toward the lip. [; and

~~— a precipitating agent within the reservoir, wherein the precipitating agent is a salt of a multivalent cation or a multivalent organic acid.]~~

9. (Currently amended) The spittoon of claim [8] 26, wherein the precipitating agent is incorporated in an absorbent pad within the reservoir.

10. (Currently amended) The spittoon of claim [8] 26, wherein the precipitating agent is calcium nitrate or magnesium nitrate.

11. (Original) The spittoon of claim 8, wherein the lip extends inwardly around an upper perimeter of the spittoon and defines a spittoon entrance.

12. (Original) The spittoon of claim 8, further comprising a retractable lid.

13. (Original) The spittoon of claim 12, where the lid is enclosed within the spittoon when retracted.

14. (Original) The spittoon of claim 13, where, when the lid is retracted, the lid is enclosed in a portion of the spittoon that is distinct from the waste ink reservoir.

15. (Original) The spittoon of claim 8, where the reservoir is configured such that when the spittoon is tilted toward the lip at an angle up to ninety degrees, the lip retains a volume of waste ink equal to approximately one-quarter of the capacity of the waste ink reservoir.

16. (Currently amended) The spittoon of claim [4] 8, where the reservoir is configured such that when the spittoon is tilted toward the lip at an angle up to forty-five degrees, the lip retains a volume of waste ink equal to approximately one-half of the capacity of the waste ink reservoir.

A' cont.  
17. (Currently Amended) An inkjet printer, comprising a printhead and a printhead service station, the service station including a spittoon with a bottom and one or more walls, each wall having a top edge, the walls in combination with the bottom defining a waste ink reservoir, a lip that extends inwardly from at least one wall configured to retain a volume of waste ink when the spittoon is tilted toward the lip, an absorbent pad within the reservoir; and a precipitating agent incorporated in the absorbent pad, wherein the precipitating agent is selected to react with a component of the waste ink to form a precipitate.

18. (Original) The printer of claim 17, wherein the absorbent pad incorporates one or more precipitating agents that are magnesium salts or calcium salts.

19. (Original) The printer of claim 17, where the service station includes one or more pen caps and one or more pen wipers.

20. (Original) The printer of claim 17, where the spittoon further comprises a retractable lid that is enclosed within the spittoon when retracted, where the lid is configured to be opened and closed automatically by the printer.

21. (Original) An inkjet printing mechanism, comprising:  
means for spitting ink into a spittoon;  
means for retaining said previously spit ink within said spittoon during tilting of  
said inkjet printing mechanism at an angle of up to 45 degrees; and  
means within said spittoon for initiating a precipitation reaction with at least  
one component of said previously spit ink.

22. (Original) A method of utilizing a spittoon in an inkjet printing  
mechanism, comprising:

*A<sup>1</sup> cont.*  
spitting ink into the spittoon positioned in a spit orientation;  
accumulating a supply of ink in said spittoon;  
precipitating at least one component of said ink in said spittoon;  
removing said spittoon with said supply from the inkjet printing mechanism;  
during said removing, tilting said spittoon from said spit orientation; and  
during said tilting, retaining said supply within said spittoon.

23. (Original) The method of claim 22, wherein said spittoon is tilted at up  
to 90 degrees.

24. (Original) The method of claim 22, wherein said spittoon is tilted in  
more than one direction.

25. (Original) The method of claim 22, further comprising dumping said  
supply and replacing said spittoon in said inkjet printing mechanism.

*A<sup>2</sup>*  
26. (New claim) The spittoon of claim 8, further comprising a precipitating  
agent within the reservoir, wherein the precipitating agent is a salt of a multivalent  
cation or a multivalent organic acid.